

Repair of Diverter Valve Saves More Than 90% Of the Replacement Cost!

ENECON's International Engineering Team, based in Singapore, completed a rebuilding work of a 3-way diverter valve for one of the local power stations. The valve was badly corroded and the thread for the 3 ports (near the flange) were badly worn and/or damaged. The rebuilding work involved 3 different processes.

1. Re-welded and re-threaded the 3 ports.
2. The port O-ring sleeves were undercut and rebuilt with DurAlloy and machined to tolerance.
3. The entire internal surface was protected with CeramAlloy CL+.

The power plant engineer said that to replace the valve would cost about \$35,000. The ENECON repair cost the power station only \$3,000.

ENECON Singapore Pte Ltd

The Fluid Flow
Systems Specialists

24 Liu Fang Road
Singapore 2262

Tel. (65) 2662229
Fax. (65) 2661110

20 August 1994

ENECON Corporation

Dear Mike,


We have just completed a rebuilding work of a 3-way diverter valve for one of our power station. The valve was badly corroded and the thread for the 3 ports (near the flange) were badly worn and/or damaged. The rebuilding work involves 3 different process.

1. Re-welded and re-thread the 3 ports.
2. The port O-ring sleeve were undercut and rebuild with DurAlloy and machine to tolerance.
3. The entire internal surface was protected with CeramAlloy CL+.

I was told by the engineer that to replace a new valve will cost around S\$35,000.00 (US\$23,000.00). The repair and rebuilding cost the power station only S\$3,300.00 (US\$2,170.00). They will monitor the performance of our materials and proceed to have all their diverter valve protected with our CeramAlloy CL+ if it is able to protected the valve. (which I am very sure we can)

Attached copies of photographs and tender specification for your perusal.

Best regards



JEFFREY KOH